## **DR-170**

## LACQUER THINNER



This thinner is a lacquer thinner based on ketone, ester, alcohol and aromatic hydrocarbon. It is designed to be most suitable for lacquer paint.

Usage	Lacquer thinner		
	Spe	cification	
Paint type	Aromatic hydrocarbon containing ketone and alcohol		
Specific gravity	Approx. 0.85	Distilation curve	Category ℃
Appearance	Transparent liquid		Initial Boiling Point (Min.) More than 60
Storage Condition	Store indoors with good ventilation		Temperature at 50% Outflow (Max.) More than 100
Shelf life	12 months from the manufacturing date		Final Boiling Point (Max.) More than 180
	Product Properties	(Physical Property	v Data)
Lacquery paint thinner	Excellent dilution of lacquer paint		
	Но	w to Use	
How to Use	1. Add a specific amount to the lacquer paint depending on the type of work.		
Remarks	1. Wear protective gear and ventilate sufficiently to prevent inhalation by scattering.		
	2. The product is inflammable and thus vulnerable to fire. Never keep or use the product near fire.		
	Make sure to avoid sparks by impact, dropping, or friction upon handling.		
	3. Do not mix with other thinners.		
	4. Fully understand the MSDS before handling the product.		

## NOROO 노루페인트