

# Q-fit CLEAR COAT



This product is a water-based transparent paint mainly made of special acrylic emulsion which is excellent in water resistance and weather resistance, and is applied to exterior wall coating and graphic design top coat to help maintain colors for a long term. In addition, anyone can paint with ease because it is less smelling and does not have to be diluted at the time of coating.

Usage

Outside wall paintings and graphic design top coat, dryvit top coat

## Specification

Paint type	Water-based acrylic type/Top coat transparent			
Drying time	Category	5°C	20°C	30°C
	Dry-hard	5 hours	2 hours	1 hour
	Time required for re-coating (min.)	6 hours	4 hours	3 hours
Thinner	No dilution recommended (tap water if necessary)	Coating Method	Brush, roller, spray coating	
Specific gravity	Approx. 1.0±0.1	Solid volume ratio	Glossy - 27.2 %, Matte - 23.5%	
Theoretical Coverage	12~15 m <sup>2</sup> /ℓ	Thickness of dried film	20μm	
Gloss	Glossy, matte	Color	Transparent	
Storage and preservation	12 months (Dry, cool, and dark place with good ventilation, room temperature 5°C~30°C, humidity less than 80%)			

## Product Properties (Physical Property Data)

Durability	Water resistance and alkali resistance are superior, and the initial coating appearance is maintained for a long period of time.
Environmental impact	Environmental mark certified.

## How to Use

Surface treatment	<ol style="list-style-type: none"> <li>The material should be sufficiently cured (cured more than 30 days at 20°C)</li> <li>Laitance, dust, oil and other contaminants on the surface must be completely removed.</li> <li>The proper pH of the material must be less than 9, and the percentage of moisture content must be less than 6%.</li> </ol>
Coating Method	<ol style="list-style-type: none"> <li>Primer                     <ol style="list-style-type: none"> <li>After the surface treatment, apply 15μm D.F.T. of waterbased sealer DNX-4001 with a roller or a brush.</li> <li>For areas where the absorption of the surface is severe apply once more.</li> </ol> </li> <li>Color top coat                     <ol style="list-style-type: none"> <li>Apply water-based paint uniformly that gives color so the original surface is concealed.</li> </ol> </li> <li>Transparent top coat                     <ol style="list-style-type: none"> <li>Apply Q-fit CLEAR COAT after the color paint is completely dry.</li> </ol> </li> </ol> <p>- When applying rollers, apply thinly with an oily roller with short hair.(Refer to the precautions for painting)</p>