

DR-610

INORGANIC ETHYL SILICATE PRIMER THINNER

This thinner is based on aromatic hydrocarbon and made to best exhibit the physical properties of inorganic silicate primer (DHDC-1800 Series).

Usage

Thinner for inorganic ethyl silicate primer coating

Specification

Paint type	Aromatic hydrocarbon		
Specific gravity	Approx. 0.8	Initial Boiling Point	(Min.) 108°C
Appearance	Transparent liquid	Temperature at 50% Outflow	(Max.) 162°C
Flash point	At least 7°C	Final Boiling Point	(Max.) 187°C
Storage Condition	Store indoors with good ventilation		
Shelf life	12 months from the manufacturing date		

Product Properties (Physical Property Data)

Thinner Properties	Excellent dilution of inorganic ethyl silicate primer
--------------------	---

How to Use

How to Use	1. Add a specific amount to the inorganic ethyl silicate primer depending on the type of work.
Remarks	1. Wear protective gear and ventilate sufficiently to prevent inhalation by scattering. 2. The product is inflammable and thus vulnerable to fire. Never keep or use the product near fire. Make sure to avoid sparks by impact, dropping, or friction upon handling. 3. Do not mix with other thinners. 4. Fully understand the MSDS before handling the product.

NOROO 노루페인트