

CHEMUV WOOD SEALER WHITE



CHEMUV WOOD SEALER WHITE is a UV-curable paint for wood primer and mainly consists of light-curable resin along with photoinitiator, extender pigment, and additives. It features outstanding grain filling, concealment, adhesiveness and superior physico-chemical properties of the film.

Usage

UV-curable paint for primer wood such as MDF and plywood

Specification

Paint type	UV-curable Paint		
Product features	1. This UV wood sealer features outstanding grain filling and concealment. 2. It is a UV-curable paint that does not have pot life limitations. 3. It is good for roll coater application.		
Exterior	White liquid	Color	White
Specific gravity (25 °C)	1.45 ± 0.05 (For white)	UV-curing conditions	300 ± 100 mJ/cm ²
Coverage (g/m ²)	30 ± 10	Solid content (%)	Over 95 %
Viscosity (KU/25 °C)	125 ± 5	Shelf life	6 months
Thinner	UV thinner for plywood		

How to Use

Surface treatment	1) Do not paint on wet wood. 2) Completely remove oil, moisture, sand, dust and foreign substances from the surface. 3) Apply the wood sealer after checking the surface painted with the primer.
Coating Method	1. Coating Method 1) Use RRC (Reverse roll coater), DRC (Direct roll coater) to roll sufficient amount of UV Wood Sealer White and paint 2 - 4 times. 2. Drying conditions 1) UV drying condition is 300 ± 100 mJ/cm ² . 2) Instructions above may vary depending on type of basis material and line conditions. * Please inquire the technical department prior to using this product to understand the handling and painting precautions.

► This data sheet is based on the test results and knowledge that NOROO produced or possesses, and may change without notice for quality improvement.