

AQUAWOOD SANDING SEALER



AQUAWOOD SANDING SEALER is a waterborne paint made of special waterborne resin that features physical property like weather resistance and additives that have excellent preservative and anti-germ effects. It helps wood maintain its natural features and enhance weather resistance, workability, anti-germ effect, anti-distortion and anti-cracks.

Usage

Primer for wood interior, furniture

Specification

Paint type	Waterborne paint			
Product features	1. Eco-friendly waterborne primer 2. Excellent sanding 3. Preservative effect 4. Excellent adhesion 5. Spreading into substrates.			
Exterior	Milk color liquid	Drying (20 °C)	Set to touch drying	Within 30 minutes
Specific gravity (25 °C)	1.05 ± 0.05		Hardening	72 hours
Coverage (g/m²)	40 - 60	Viscosity (KU/25 °C)	80 ± 5	
Color	Transparent	Solid content (%)	32 ± 5	
Mixture ratio	BASE : H2O = 100 : 10~20			

How to Use

Surface treatment	1) Do not paint on wet wood. 2) Completely remove oil, moisture, sand, dust and foreign substances from the surface.
Coating Method	1) After the surface treatment dip or spray sanding sealer. 2) In this phase use it stir to be mixed uniformly. 3) When applying the second sanding sealer, if the first application is fully dried, you have to sand with P400. 4) After the sanding sealer, have dry time at least 6~8 hours (1~2 hours/60°C) then apply the topcoat. 5) When applying the second topcoat, if the first application is fully dried, you have to sand with P400. 6) Please pack after complete dry. If it is packed not completely, it can stick to other surfaces.

► This data sheet is based on the test results and knowledge that NOROO produced or possesses, and may change without notice for quality improvement.

NOROO 노루페인트