

# SOON&SOO ONE-TOUCH DIY



Soon&Soo one-touch DIY paint is a premium paint that can reduce labor costs and shorten the construction period by providing hiding and durability with only one coat, unlike general water-based paints that recommend the existing two coats. In addition, it is an eco-friendly type of water-based paint containing few volatile organic compounds and heavy metals in addition to having little odor in painting and drying processes. As it is designed based on a special emulsion resin with excellent adhesion and pigment, it is a superior multi-purpose, highly functional water-based paint with excellent stain resistance due to its soft egg-shell luster that can be applied to various materials including not only concrete but also old coating of existing oil-based enamels and lacquers.

Usage	Alkaline material such as concrete, cement mortar, plasterboard, etc. Interior wood, enamel/lacquer old coating repairs
-------	--

## Specification

Paint type	Acrylic emulsion water-based interior / Top coat			
Drying time	Category	5℃	20℃	30℃
	Set-to-touch	1 hour	30 minutes	20 minutes
	Dry-hard	3 hours	2 hours	1 hour
	Time required for re-coating (min.)	4 hours	3 hours	2 hours
Thinner	Tap water(dilution rate: up to 10%, volume ratio)	Coating Method	Brush, roller, spray coating	
Specific gravity	Approx. 1.37(based on white color)	Solid volume ratio	Approx. 39%(based on white color)	
Theoretical Coverage	6~8㎡/ℓ/2times	Thickness of dried film	50μm (1coat recommended)	
Re-coating interval	20℃, sufficient ventilation for a minimum of 3 hours	Color	White, light colour	
Gloss	Egg-shell			
Storage and preservation	12 months (Dry, cool, and dark place with good ventilation, room temperature 5℃~30℃, humidity less than 80%)			

## Product Properties (Physical Property Data)

Various purposes	Multi-purpose water-based paint that can be attached to various basis materials and has superior stain resistance.
Eco-friendly properties	A LOW VOC, harmful heavy metal free, British Allergy UK certified, and environmental mark certified product.
Excellent hiding power	Due to its excellent hiding power, the work time can be shortened, and it has an anti-fungal function.

## How to Use

Surface treatment	<ol style="list-style-type: none"><li>1. If there are dust, oil, scribbles in crayons, colored pencils, etc. and dirty finger marks, they should be removed with a neutral detergent diluent the surface should be wiped.</li><li>2. Areas infested with mold should be cleaned with a damp cloth after removing the mold using bleach or a mold cleaner. The paint should be applied after completely drying the surface.</li><li>3. If any of the old film remains, apply the paint after sanding the old film with sanding paper and clean the area for enhancement of adhesion.</li><li>4. When applied to concrete and general water-based old films, the surface treatment method is the same as the one for general water-based.</li></ol>
Coating Method	<ol style="list-style-type: none"><li>1. Primer<ol style="list-style-type: none"><li>① After surface treatment, if necessary, dilute Gesso with water up to 10%, and apply once with a roller, brush, or spray to get a dry film thickness of 30μm.</li></ol></li><li>2. Top Coat<ol style="list-style-type: none"><li>① After at least 3 hours at 20°C following undercoating, apply this paint twice to get a dry film thickness of 50μm with a brush, roller or spray.</li><li>② At this time, apply by diluting with water up to 10%.</li></ol></li></ol>