## **COLOR MIX (SOLVENT-BASED)**

## Tinter for solvent-based paint

COLOR MIX (SOLVENT-BASED) is a high-quality tinter for solvent-based paints that can realize various colors. This product is able to realize various colors of high chroma by using pigment with excellent distinctness of image. It has excellent coloring power, so it can be toned to a dark color even with a small addition. It is also excellent in weather resistance and compatibility, and can be widely used in most solvent-based paints. It does not contain harmful heavy metal pigments such as lead and chrome.

Usage	Tinter for solvent-based paint
Specification	
Paint type	Solvent-based tinter
Applied paint	Enamel, ready mixed, lacquer etc. 1K solvent-based paint
	Acrylic urethane, epoxy etc. 2K solvent-based paint
Amount used	Less than 3%(Volume ratio, based on white color paint)
Color	Special red, reddish brown, iron yellow, bright yellow, bright green, bright blue, black, violet etc.
Specific gravity	0.95 ~ 1.91 (Varies depending on the color)
Packging unit	0.1L
Storage and preservation	12 months (well-ventilated dry, cold and dark location, room temperature 5°C~30°C)
How to Use	
Coloring	<ol> <li>Use after evenly mixing this tinter before coloring.</li> <li>Mix the colors by adding a small amount of tinter to the paint to be used for coloring, while checking the color change.</li> <li>Color differences before and after drying may occur depending on the product.         <ul> <li>please check the color change after drying.</li> </ul> </li> <li>The color may look different depending on the light source. So, check the color in accordance with the coating conditions if possible.</li> <li>Upon coloring, add the tinter while stirring the paint to be used for coloring.</li> <li>Stir the paint uniformly immediately after adding the tinter.</li> <li>Sufficiently stir the paint until the tinter is completely mixed.</li> </ol>
Remarks	<ol> <li>As it is a tinter for solvent-based paint, it cannot be used for water-based paint.</li> <li>As this product is a tinter, it cannot be applied by itself.</li> <li>As this product has excellent tinting power, use it by adding a small amount at a time.</li> <li>For acrylic paints or vinyl paints among solvent paints, the compatibility should be checked with our technical team before use.</li> <li>In the case of 2K paints, add the hardener after completion of coloring.</li> <li>In the case of excessive use, water resistance, gloss decline, and delay in drying may occur. Therefore, for toning of darker colors, please contact our technical team.</li> </ol>