

ALL-NEW COLOR STAIN

Antisptic for wood



This product is designed to prevent the aging of wood from moisture by simply applying it to wooden products such as floorboards, containers, and the back side of sinks without a complicated special treatment. Painted timber is sometimes resistant to shrinkage, blistering and mold, even when exposed to rain or other moisture. However, it is difficult to expect satisfactory results for continuous contact with the ground surface, or for harsh conditions of prolonged wetting.

Usage

Wood houses wood for construction

Specification

Paint type	Oil stain			
Drying time	Category	5°C	20°C	30°C
	Set-to-touch		8 hours	
	Dry-hard		36 hours	
	Time required for re-coating (min.)		12 hours	
Thinner	Use of undiluted solution	Coating Method	Brush, roller, spray coating.	
Specific gravity	Approx. 0.9±0.10	Solid volume ratio	22±1 %	
Theoretical Coverage	5~6m ² /ℓ/2times	Thickness of dried film		
Re-coating interval	20°C, sufficient ventilation for a minimum of 12 hours	Gloss	Matte(Permeated to wood)	
Color	Transparent			

Product Properties (Physical Property Data)

Beautiful appearance	The dry film appearance is beautiful due to the vivid wood grain.
Mildew-resistant effect	It has antibacterial, antiseptic, and wood protection effects.
Excellent permeability	It has a high wood protection effect due to its soft luster and superior permeability.

How to Use

Surface treatment	<ol style="list-style-type: none">1. Smooth the rough surface of the substrate by grinding it with sandpaper #180-220 along the grain.2. Completely clean grease or contaminants and abrasion powder on the surface of the substrate and thoroughly dry it.3. Thoroughly dry the wet wood and completely remove the mold before coating.
Coating Method	<ol style="list-style-type: none">1. Apply without dilution.2. After finishing the base treatment, apply the COLOR STAIN CLEAR using coating equipment. (brush, roller, spray, etc.)3. After 12 hours at 20°C following one coat, proceed with an additional coat.4. Do not coat thickly at once if a brush or roller is used, but apply thinly many times.