

# ALL-NEW COLOR STAIN COVER UP



This product is a hiding-type stain for wood that is composed mainly of special resins and pigments. It is a paint that prolongs the life of wood by having antimicrobial and preservation effects for wood and preventing discoloration and distortion by water or ultraviolet rays. It has good color reproducibility regardless of the wood species and is excellent in repair painting and workability because there is little color difference in the overlapping part of painting.

Usage

Wood houses wood for construction

## Specification

Paint type	Oil stain		
Drying time	Category	5°C	20°C
	Set-to-touch		8 hours
	Dry-hard		36 hours
	Time required for re-coating (min.)		12 hours
Thinner	Use of undiluted solution	Coating Method	Brush, roller, spray coating.
Specific gravity	Approx. 1.0±0.10	Solid volume ratio	29±1 %
Theoretical Coverage	5~6m <sup>2</sup> /ℓ/2times	Thickness of dried film	
Re-coating interval	20°C, sufficient ventilation for a minimum of 12 hours	Gloss	Matte(Permeated to wood)
Color	Brown		

## Product Properties (Physical Property Data)

Workability	Color reproducibility is good regardless of the wood species.
Workability	Repair coating and workability are excellent by applying a little hiding power.
Mildew-resistant effect	It has antibacterial, antiseptic, and wood protection effects.

## How to Use

Surface treatment	<ol style="list-style-type: none"> <li>1. Smooth the rough surface of the substrate by grinding it with sandpaper #180-220 along the grain.</li> <li>2. Completely clean grease or contaminants and abrasion powder on the surface of the substrate and thoroughly dry it.</li> <li>3. Thoroughly dry the wet wood and completely remove the mold before coating.</li> </ol>
Coating Method	<ol style="list-style-type: none"> <li>1. Apply without dilution.</li> <li>2. After finishing the base treatment, apply the other colors COLOR STAIN COVER UP using coating equipment. (brush, roller, spray, etc.)</li> <li>3. After 12 hours at 20°C following one coat, proceed with an additional coat.</li> </ol>