

YEGREENA ELASTIC PAINT

Intermediate coating

This product is an interior-only elastic paint that is composed mainly of elastic acrylic resin and pigment. Two colors are painted at the same time to form a sensation of a beautiful color. It is excellent in water resistance, alkali resistance and mold resistance while maintaining the beautiful appearance of a building for a long period of time.

Usage

Multicolor pattern elastic paint for interior of buildings
Non-extended balcony inside of apartments

Specification

Paint type	Water-based acrylic type		
Drying time	Category	5°C	20°C
	Set-to-touch		3 hours
	Dry-hard		24 hours
Thinner	Tap water(dilution rate: up to 5%, volume ratio)	Coating Method	Exclusive spray gun
Specific gravity	Approx. 1.1±0.1	Solid volume ratio	Approx. 33%
Theoretical Coverage	0.66 m ² /L	Thickness of dried film	500μm
Gloss	Glossy	Color	Other colors
Storage and preservation	12 months (Dry, cool, and dark place with good ventilation, room temperature 5°C~30°C, humidity less than 80%)		

Product Properties (Physical Property Data)

Excellent workability	Intermediate (pattern formation) coating is easy by one finish coat.
Excellent film property	Water resistance, and alkali resistance are excellent.
Environmental impact	It is an eco-friendly product having almost no VOC and odor. This product has obtained Eco-Mark certification.
Crack resistance	The elasticity of the film prevents microcracks of buildings.
Beautiful appearance	Imparts a beautiful appearance by mixing two colors.

How to Use

Surface treatment	<ol style="list-style-type: none">The material should be sufficiently cured (cured more than 30 days at 20°C)Laitance, dust, oil and other contaminants on the surface must be completely removed.The proper pH of the material must be less than 9, and the percentage of moisture content must be less than 6%.The gaps and grooves on the surface must be filled with exterior water-based putty, and surface adjustment should be made before coating.
Coating Method	<ol style="list-style-type: none">Primer<ol style="list-style-type: none">Uniformly apply the CLEAR SEALER, which is a specified undercoat, or coat MIXING LIQUID on the base surface once.Intermediate coating<ol style="list-style-type: none">After the undercoat is completely dried, apply the ceramic coat for intermediate coating with a special gun.Upon spray coating, be sure to work perpendicular to the coating surface to obtain a uniform pattern.Upon using an intermediate coat, dilute with water to less than 5%, and use after sufficient stirring as it is a high viscosity paint.Top Coat<ol style="list-style-type: none">Apply YEGREENA ELASTIC PAINT(top coat) once after the intermediate coating material has completely dried for mold resistance.