

SOON & SOO GESSO ^{SUPER}

SOON & SOO GESSO ^{SUPER} that can be used on various indoor materials (smooth film surface, wood, tile, steel) with strong adhesion

SOON & SOO GESSO ^{SUPER} is a high-quality super strong interior water-based primer with excellent adhesion and hiding power. It is applied to almost all materials in daily life, beyond the range of use of existing gesso (wallpaper, wood, concrete, etc.) to hard and smooth substrates (glass, steel, tile, plaster board, film paper, etc.).

SOON & SOO GESSO ^{SUPER} Powerful even on hard and smooth substrates

Usage For pretreatment of concrete, cement mortar, plaster board, tile, adhesive sheet
Repair of coated steel, interior wood, enamel/lacquer old coatings etc.



Strong adhesion and hiding power to any interior material!

SOON & SOO GESSO ^{SUPER}, a multipurpose, high-quality gesso that can be applied to existing oil-based enamel or lacquer coatings



SOON & SOO GESSO *SUPER*

SOON & SOO GESSO *SUPER*

Powerful even on hard and smooth substrates

SOON & SOO GESSO *SUPER* that can be used on various indoor materials (smooth film surface, wood, tile, steel) with strong adhesion



QR code
for product guide



SOON & SOO GESSO *SUPER*, Advantages



Strong adhesion

Excellent adhesion to various substrates such as hard and smooth substrates



Excellent whiteness and hiding power

Improved workability such as excellent hiding power, quick drying, and spreadability



Eco-friendliness

Environmental label certification, safe as a water-based product

SOON & SOO GESSO *SUPER*, Adhesion Test

※International standard ASTM D3359 test

	Steel plate	PET film	glass	tile	plastic	high gloss plaster board
Strong adhesion to various substrates!						
SOON & SOO GESSO <i>SUPER</i>	Good	Good	Good	Good	Good	Good

SOON & SOO GESSO *SUPER*, Property DATA Comparison / Characteristics

88.7	91.8	96	98	Paint type	Acrylic emulsion water-based interior / Primer
Company A	SOON & SOO GESSO <i>SUPER</i>	Company A	SOON & SOO GESSO <i>SUPER</i>	Thinner	Tap water(dilution rate: up to 10%, volume ratio)
Whiteness (%)		Hiding power (%)		Coating Method	Brush, roller, spray coating
				Specific gravity/ Solid volume ratio	Approx. 1.44 / Approx. 37 % (Based on white color)
				Theoretical Coverage	9~12 m ² / l /1time
				Thickness of dried film	30μm (1 coat recommended)
				Color/Gloss	White/Matte
				Storage and preservation	12 months (well-ventilated dry, cold and dark location, room temperature 5℃~30℃, humidity less than 80%)



Is there a GESSO that will help paint better, last longer and produce prettier colors on painted surfaces?



SOON&SOO GESSO *super*

Super strong water-based gesso for interior with excellent adhesion and hiding power!