

PANTONE AIRFRESH



PREMIUM PAINT INSPIRED BY PANTONE

※ This product can be used inside multi-use facilities and 100-500 unit apartment houses under The Indoor Air Quality Control Act.

Pantone Airfresh is a matt paint for wallpaper and concrete which has the air purification function through the physical and chemical absorption of volatile organic compounds especially formaldehyde. Airfresh has very little odor during the painting and drying process, and is a high-functional paint with an antibacterial mark.

Usage	Interior silk of apartments, commercial buildings, schools, hospitals, officetels, etc., and wall paper repair and concrete finishing
-------	---

Specification

Paint type	Acrylic emulsion water-based interior / Top coat			
Drying time	Category	5°C	20°C	30°C
	Dry-through	3 hours	2 hours	1 hour
	Time required for re-coating (min.)	4 hours	3 hours	2 hours
Thinner	Tap water(dilution rate: up to 20%, volume ratio)	Coating Method	Brush, roller, spray coating.	
Specific gravity	Approx. 1.44(Based on white color)	Solid volume ratio	34.5 % (Based on white color)	
Theoretical Coverage	8.6 m ² /ℓ/1time	Thickness of dried film	40μm (1 coat recommended)	
Re-coating interval	20°C, sufficient ventilation for a minimum of 3 hours	Color	White, other colors	
Gloss	Matte	Package	1L	
Storage and preservation	12 months (well-ventilated dry, cold and dark location, room temperature 5°C~30°C, humidity less than 80%)			

Product Properties (Physical Property Data)

Air purification	It absorbs formaldehyde chemically and physically to purify the air
Excellent antimicrobial properties	Anti-bacterial and anti-fungal effects are excellent.
Eco-friendly properties	Environmental mark certified product

How to Use

Surface treatment	<ol style="list-style-type: none">1. For areas that are torn or poorly adhered, recuperation is necessary by using an adhesive for wallpaper so that there are no cracks.2. If there are scribbles in crayons, colored pencils, etc. and dirty finger marks, they should be removed with a neutral detergent diluent and a soft cloth, and the surface should be wiped.3. Areas infested with mold should be cleaned with a damp cloth after removing the mold using bleach or a mold cleaner. The paint should be applied after completely drying the surface.4. When applied to concrete and general water-based old films, the surface treatment method is the same as the one for general water-based paints.
Coating Method	<ol style="list-style-type: none">1. Apply 1~2 coats with a brush, roller or spray.2. After 2 coats, the re-coating interval is at least 3 hours after the first top coating at 20°C.3. If the subsequent coating is applied on the dried film of Airfresh, the air purification function will not be availal