

GREEN VARNISH

NEW DV-2800



※ This product can be used inside multi-use facilities and 100-500 unit apartment houses under The Indoor Air Quality Control Act.

This product is a varnish composed mainly of urethane, thus it dries fast and has excellent flexibility, abrasion resistance, water resistance, and durability along with good workability. It is a air-drying type one-component fast-drying varnish that can be applied widely to new basis materials or old films.

Usage

Wood inside buildings & furniture, floors, paper floors, wood doors, wood window frames

Specification

Paint type	Alkyd urethane			
Drying time	Category	5°C	20°C	30°C
	Dry-hard	5 hours	3 hours	2 hours
	Time required for re-coating (min.)	10 hours	8 hours	4 hours
Thinner	DR-291(dilution rate: less than 10%, volume ratio)		Coating Method	Brush, roller, spray coating
Specific gravity	Approx. 0.9		Solid volume ratio	45%
Theoretical Coverage	15m ² /ℓ/1time		Thickness of dried film	30μm (Based on 1time)
Re-coating interval	20°C, sufficient ventilation for a minimum of 8 hours		Gloss	Glossy
Color	Transparent			

Product Properties (Physical Property Data)

Beautiful appearance	The dry film appearance is beautiful due to the vivid wood grain.
Film property	Abrasion resistance, water resistance and durability are excellent.

How to Use

Surface treatment	<ol style="list-style-type: none">1. Smooth the rough surface of the substrate by grinding it with sandpaper #180-220 along the grain.2. Completely clean grease or contaminants and abrasion powder on the surface of the substrate and thoroughly dry it.3. Thoroughly dry the wet wood and completely remove the mold before coating.
Coating Method	<ol style="list-style-type: none">1. Do not apply thickly at once. After dilution, apply 2-3 thin and even coats using spray or brush.2. Please use the recommended thinner (DR-291).

NOROO 노루페인트