GREEN VARNISH



NEW DV-2800F

This product is a varnish composed mainly of urethane, thus it dries fast and has excellent flexibility, abrasion resistance, water resistance, and durability along with good workability. It is a air-drying type 1K matte gloss varnish that can be applied widely to new basis materials or old films.

Usage	Wood inside buildings & furniture, floors, paper floors, wood doors, wood window frames						
Specification							
Paint type	Alkyd urethane						
Drying time	Category	5°C			0℃	30℃	
	Dry-hard	5 ho	urs	3 hours		2 hours	
	Time required for re- coating (min.)	10 hc	ours	8 hours		4 hours	
Thinner	DR-291(dilution rate: less t volume ratio)	dilution rate: less than 10%, ratio)		Coating Method		Brush, roller, spray coating	
Specific gravity	Approx. 0.9		Solid vol	ume ratio	44%		
Theoretical Coverage	14.7 m²/l/1time		Thickness of	of dried film	30μm (Based on 1time)		
Re-coating interval	20℃, sufficient ventilation for a minimum of 8 hours		Gloss		Matte		
Color	Transparent						
Product Properties (Physical Property Data)							
Beautiful appearance	The dry film appearance is beautiful due to the vivid wood grain.						
Film property	Abrasion resistance, water resistance and durability are excellent.						
How to Use							
Surface treatment	 Smooth the rough surface of the substrate by grinding it with sandpaper #180-220 along the grain. Completely clean grease or contaminants and abrasion powder on the surface of the substrate and thoroughly dry it. Thoroughly dry the wet wood and completely remove the mold before coating. 						
Coating Method	 Do not apply thickly at once. After dilution, apply 2-3 thin and even coats using spray or brush. Please use the recommended thinner (DR-291). 						