

NRP-Pt1000gf

Silicone adhesive



NRP-Pt1000gf is a two-component additive silicone adhesive which is suitable for making various protective films.

Usage

Silicone adhesive

Specification

| | | | |
|------------------|--|--------------------|--|
| Product type | Two-component silicone adhesive | | |
| Product features | <ol style="list-style-type: none">1. It features outstanding workability such as leveling and defoaming.2. It features outstanding reworkability.3. It features outstanding surface spread property. | | |
| Thinner | Toluene, MEK, nucleic acid | Pot time (25 °C) | 1 day |
| Exterior | Transparent liquid | | |
| Viscosity | 300 ± 50 | Curing conditions | 2 - 5 minutes at 130 °C |
| Specific gravity | 0.95 ± 0.05 | UL-certified | Not certified |
| Solid | 63 ± 1 % | Storage conditions | Store in a shaded indoor space with sufficient ventilation. |
| Mixing ratio | Base : Hardener = 50 : 1 | Shelf life | 6 months from the manufacturing date (when stored at room temperature) |

Product Properties (Physical Property Data)

| | |
|--------------|---------------------------------------|
| Adhesiveness | 900 - 1100 gf/cm ² (30 μm) |
|--------------|---------------------------------------|

How to Use

| | |
|------------|--|
| How to Use | <ol style="list-style-type: none">1. Apply the product on the substrate.2. Dry according to the designated curing conditions. |
| Note | <ol style="list-style-type: none">1. Instructions above may vary depending on the type of substrate and the painting line conditions.2. Please refer to the MSDS when handling the product. |

► The data shown above were obtained under the laboratory conditions, and the product properties may vary depending on work method and circumstances. Please refer to the property data listed above only as reference.

NOROO 노루페인트