

IMPREGNATION REMOVER-NT

Thinner

Impregnation Remover-NT is a transparent insulating varnish remover that has low toxicity and is composed of a special organic solvent. This is a superior remover product that has low toxicity unlike traditional removers. The product penetrates into the paint film and peels it off in a short period of time using a chemical method.

Use

Remover for peeling off dried varnish from the hanger

Specifications

Type of varnish	Organic solvent
Product features	1. It features superior peeling performance. 2. It has a high flash point and therefore a low fire risk.
Thinner	None
Exterior	Transparent
Specific gravity	1.19 ± 0.02
UL-certified	Not certified
Storage conditions	Store in a shaded indoor space with sufficient ventilation.
Shelf life	6 months from the manufacturing date

How to Use

How to Use	1. Dip the hanger with dried varnish in the product and remove the dried varnish on the hanger after 24 hours.
Things to Note	1. Please perform sufficient ventilation to prevent breathing of the product due to dispersion during use. 2. The container may inflate if the product is exposed to direct sunlight or heat during storage. Store the product in a shaded indoor space with sufficient ventilation. 3. Use a scraper or other appropriate tool to remove dried varnish and wash it off with water.

► The data shown above were obtained under the laboratory conditions, and the product properties may vary depending on work method and circumstances. Please refer to the property data listed above only as reference.

NOROO 노루페인트