



NOROO

NOROO Paint & Coatings

It provides
a waterproofing/
flooring that dries
within 60 seconds.

Protech

Protech NP-200(KS Certification)
Protech NH-290

There is no waterproofing/flooring
which are superior to our products

- ➔ Ultra fast hardening(drying time reduction)
- ➔ Sanitation and safety certificate(KC)
- ➔ Strong and diversified waterproofing
and flooring physical properties

KS F 4922 (Polyurea resin waterproofing) Certification



NOROO Paint & Coatings Co., Ltd.

Protech

Polyurea Coating System Protech

The waterproofing system forms the coating by spraying under high temperature and high pressure. There are two types—the pure polyurea type (Protech NP-200) and the hybrid type (Protech NH-290). The coating is dried within a few seconds after applying. It has good adhesion, elongation and flexibility. In particular, Protech NP-200 is a standard type, which has acquired the KS F 4922 (Polyurea resin waterproofing) Certification, and Protech NH-290, the hybrid type is an economical high-hardness waterproofing and flooring.

Applications


- Flooring and waterproofing for parking lots, chemical factories, stadium stands, sports facilities, etc.
- Steel structures such as steel pipes, chemical tanks, maritime structures, etc.
- Water treatment facilities, sculptures, vehicle cargo floors, etc.



Drying time

Division	5°C	20°C	30°C
Set to touch	Within 1 minute		
Dry hard	Within 60 minutes		

Painting equipment / KS and KC certifications



Features



Excellent quality

- **KS F 4922 (Polyurea resin waterproofing) Certification**
- Satisfies the Korea Water & Wastewater Works Association (KWWA) drinking water migration test standards (It is scheduled to acquire the KC certification.)

Outstanding physical properties

- Excellent elasticity, impact resistance, abrasion resistance and durability
- Excellent adhesion, chemical resistance, thermal resistance, acid resistance and cold resistance
- 100% solids contents (Solvent and VOC free), eco-friendly product

Easy workability (Urea spray equipment is required)

- Easy application to floor, vertical and inclined surfaces
- Workable under unfavorable conditions (cold weather)
- Easy to control dry film thickness and provides non-slip appearance
- Save the construction period through ultra fast hardening after spraying

Theoretical coverage : 2.2kg/m² (2mm)

※ Fully understand the instructions of the technical data package and the warnings & cautions before using the product.

NOROO Paint & Coatings Co., Ltd.

351 Bakdal-ro, Manan-gu, Anyang-si, Gyeonggi-do, KOREA Tel. 82 31 467 6408 Fax. 82 31 448 2085

www.noroo paint.com

• Issued date : March 2016 • Catalogue No : OS3-2326