

# YEGREENA VINTAGE



This product is a mixture of acrylic emulsion, lightweight filler, and color marble powder, which is a cement texture finish with a sophisticated sense and comfortable vintage style. It is an eco-friendly finishing material that can express various types of concrete stain textures according to the construction method and can create a space only for you.

Usage

Interior walls and ceilings of commercial spaces, residential spaces, etc.

## Specification

Paint type	Water-based acrylic type			
Drying time	Category	5°C	25°C	30°C
	Set-to-touch		4 hours	
	Dry-hard		24 hours	
	Time required for re-coating (min.)		12 hours	
Thinner	Tap water(dilution rate: up to 10%, volume ratio)	Coating Method	Hera, trowel coating	
Specific gravity	Intermediate coating : Approx. 1.7±0.1, Top coat : Approx. 1.1±0.1	Solid volume ratio	Intermediate coating : 46.9%, Top coat : 19.3%	
Theoretical Coverage	Intermediate coating : 0.6~0.8 m <sup>2</sup> /2times, Top coat : 10~13m <sup>2</sup> /L	Thickness of dried film	Intermediate coating : 1mm (2coats recommended), Top coat : 15µm	
Re-coating interval	20°C, sufficient ventilation for a minimum of 12 hours	Color	Gray, bright gray	
Gloss	Matte			
Storage and preservation	12 months (Dry, cool, and dark place with good ventilation, room temperature 5°C~30°C, humidity less than 80%)			

## Product Properties (Physical Property Data)

Workability	It is less hard during troweling because there is no feeling that the paint is being dragged.
Workability	It can be softly applied without splashing upon painting.
Beautiful appearance	Soft cement vintage texture can be expressed.

## How to Use

Surface treatment	<ol style="list-style-type: none"><li>1. The material should be sufficiently cured (cured more than 30 days at 20°C)</li><li>2. Laitance, dust, oil and other contaminants on the surface must be completely removed.</li><li>3. The proper pH of the material must be less than 9, and the percentage of moisture content must be less than 6%.</li><li>4. The gaps and grooves on the surface must be filled with exterior water-based putty, and surface adjustment should be made before coating.</li></ol>
Coating Method	<ol style="list-style-type: none"><li>1. Primer<ol style="list-style-type: none"><li>① After surface treatment, apply once with clear sealer, which is a specified undercoat of this company, or interior water-based paint.</li></ol></li><li>2. Intermediate coating<ol style="list-style-type: none"><li>① After application to the entire surface or plastering with YEGREENA VINTAGE for walls, dry for at least 12 hours.</li><li>② After evenly plastering with YEGREENA VINTAGE for walls at a thickness of about 1mm, press the trowel lightly at the contact point to naturally make patterns on the surface.</li></ol></li><li>3. Top Coat<ol style="list-style-type: none"><li>① If necessary, apply YEGREENA VINTAGE for walls once for clear top coating.</li></ol></li></ol>